ZS/H3/ZTR/150



Fuse holders
60-150 V with status display

Qty.
ZS/H3/ZTR/150
3633.2 20

5.1
60 - 150
6.3
<5
1.6

5 x 20

Page	Qty.
PMC SB 5/50 WH	
4600.7 339	500

Remarks
ZTRK 2,5... FTRK 2,5...

ZS/H4/ZTR/250



Fuse holders
140-250 V with status display

Qty.
ZS/H4/ZTR/250
3634.2 20

5.1
140 - 250
6.3
<5
1.6

5 x 20

Page	Qty.
PMC SB 5/50 WH	
4600.7 339	500

Remarks
ZTRK 2,5... FTRK 2,5...

Disconnect plug

The established disconnect-plug system has a high-quality surfaces and thus minimal contact resistance. This ensures precise, unbiased measurement readings. A variety of components can be soldered into an unpopulated test plug.

ZDS.../ZTR

Disconnect plug

Qty.
ZDS 1/ZTR
3612.2 20
Disconnect-plug with wire jumper
ZDS 2/ZTR
3613.2 20
Disconnect plug with diode
ZDS 3/ZTR
3614.2 20
Disconnect plug with diode
ZDS 4/ZTR
3615.2 20
Unpopulated disconnect plug

5.1
400
15

Soldered diode 1N4007
Reverse voltage 1000V / Current 1A

Page	Qty.
PMC SB 5/50 WH	
4600.7 339	500

Remarks
ZTRK 2,5... FTRK 2,5...

DS



Disconnect plug

Qty.
DS 1/TRK 1,5 YE
1400.2 1
Disconnect-plug with wire jumper
DS 2/TRK 1,5 YE
1401.2 1
Disconnect plug with diode
DS 3/TRK 1,5 YE
1402.2 1
Disconnect plug with diode
DS 4/TRK 1,5 YE
1403.2 1
Unpopulated disconnect plug

6
400
15

Soldered diode 1N4007
Reverse voltage 1000V / Current 1A

Page	Qty.
PMC SB 6/50 WH	
4702.7 340	500

Remarks
TRK 1,5...

GENERAL ACCESSORIES