

- True deep cycle AGM technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate and active material
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration: long cycle life & high energy density and super anti-vibration design
- Low self-discharge for longer shelf life



■ ELECTRICAL SPECIFICATIONS

Voltage (V)	Capacity (AH)					Reserve Capacity (Min)		
	100HR	20HR	10HR	5HR	3HR	@25A	@56A	@75A
6	246	224	210	192	173	490	188	135

■ PHYSICAL SPECIFICATIONS

Model	Dimensions (mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
	Length	Width	Height	Total Height			
PC6-224-GC2	260 (10.24)	180 (7.09)	247 (9.72)	253 (9.96)	30.5 (67.3)	M8	ABS

■ OPERATING TEMPERATURE RANGE

Discharge	Charge	Storage
-15°C ~ 50°C (5°F ~ 122°F)	0°C ~ 40°C (32°F ~ 104°F)	-15°C ~ 40°C (5°F ~ 104°F)


■ APPLICATIONS

Energy Storage / Renewable Energy	Boats and Ships	Solar & Wind
Recreational Vehicles	Generators	Golf Carts
Fork Lift Trucks	Motive Power	Traffic Signals
Uninterruptable Power Supplies		




Deep Cycle SLA Battery

■ Dimensions




■ Charging Profile




■ Relationship of OCV & State of Charge

$25^{\circ}\text{C} / 77^{\circ}\text{F}$



■ Cycle Life in Relation to Depth of Discharge



■ Self-Discharge Characteristic

